



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.06.2015

Version number 5

Revision: 15.06.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: **KRISTAL UHS Surfacer 53 White**
- Article number: 5329
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
No further relevant information available.
- Application of the substance / the mixture Paint
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
Kristal Coatings B.V.
Platinawerf 22B
6641 TL Beuningen - Holland
Tel: 0031 24 67 526 36
Fax: 0031 24 67 533 60
- Further information obtainable from: Product safety department: info@kristalcoatings.nl
- 1.4 Emergency telephone number:
National Poisoning Information Centre - Bilthoven - The Netherlands
T +31 (0)30 274 88 88
Restricted to physicians for information on ingredients.

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

- Flam. Liq. 3 H226 Flammable liquid and vapour.
-
- Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



GHS02

- Signal word Warning
- Hazard statements
H226 Flammable liquid and vapour.
H412 Harmful to aquatic life with long lasting effects.
- Precautionary statements
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P260 Do not breathe mist/vapours/spray.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Additional information:
EUH208 Contains Fatty acids, tall-oil, esters with polyethylene glycol mono(hydrogen maleate), compounds with amides from diethylenetriamine and tall-oil fatty acids. May produce an allergic reaction.
Restricted to professional users.
- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.06.2015

Version number 5

Revision: 15.06.2015

Trade name: **KRISTAL UHS Surfacer 53 White**

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 123-86-4	n-butyl acetate	10-25%
EINECS: 204-658-1	⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	
Reg.nr.: 01-2119485493-29		
CAS: 1330-20-7	xylene	2,5-10%
EINECS: 215-535-7	⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	
Reg.nr.: 01-2119488216-32		
01-2119486136-34	H412	
01-2119555267-33		
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	2,5-10%
EINECS: 265-199-0	⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H332; STOT SE 3, H335-H336	
Reg.nr.: 01-2119455851-35		
CAS: 100-41-4	ethylbenzene	0,5-2,5%
EINECS: 202-849-4	⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332; Aquatic Chronic 3, H412	
CAS: 222716-38-3	Fatty acids, tall-oil, esters with polyethylene glycol mono(hydrogen maleate), compounds with amides from diethylenetriamine and tall-oil fatty acids	≤ 0,5%
	⚠ STOT RE 2, H373; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	

Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Take affected persons out into the fresh air.
Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.

After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.
Remove contactlenses.

After swallowing:

Do not induce vomiting; call for medical help immediately.
Rinse out mouth and then drink plenty of water.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO₂ or powder. Fight larger fights with alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture Carbon monoxide (CO)

5.3 Advice for firefighters

Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.06.2015

Version number 5

Revision: 15.06.2015

Trade name: **KRISTAL UHS Surfacer 53 White**

(Contd. of page 2)

- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.
- **Information about storage in one common storage facility:** Store away from oxidising agents.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**

1330-20-7 xylene

IOELV Short-term value: 442 mg/m³, 100 ppm
Long-term value: 221 mg/m³, 50 ppm
Skin

100-41-4 ethylbenzene

IOELV Short-term value: 884 mg/m³, 200 ppm
Long-term value: 442 mg/m³, 100 ppm
Skin

- **DNELs**

123-86-4 n-butyl acetate

Inhalative Acute - short-term exposure - local effects	960 mg/m ³ (worker)
Acute - short-term exposure - systemic effects	960 mg/m ³ (worker)
Long-term exposure - local effects	480 mg/m ³ (worker)
Long-term exposure - systemic effects	480 mg/m ³ (worker)

1330-20-7 xylene

Dermal Long-term exposure - systemic effects	180 mg/kg bw/day (worker)
Inhalative Acute - short-term exposure - local effects	289 mg/m ³ (worker)
Acute - short-term exposure - systemic effects	289 mg/m ³ (worker)
Long-term exposure - systemic effects	77 mg/m ³ (worker)

100-41-4 ethylbenzene

Dermal Acute - short-term exposure - local effects	293 mg/kg bw/day (worker)
Long-term exposure - systemic effects	180 mg/kg bw/day (worker)
Inhalative Long-term exposure - systemic effects	77 mg/m ³ (worker)

- **PNECs**

123-86-4 n-butyl acetate

PNEC 35,6 mg/l (STP)
0,18 mg/l (aqua, freshwater)
0,36 mg/l (aqua, intermittent releases)
0,018 mg/l (aqua, marine water)

(Contd. on page 4)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.06.2015

Version number 5

Revision: 15.06.2015

Trade name: **KRISTAL UHS Surfacer 53 White**

(Contd. of page 3)

0,0981 mg/l (sediment marine water)

0,981 mg/kg (sediment freshwater)

1330-20-7 xylene

PNEC 6,58 mg/l (STP)

0,237 mg/l (aqua, freshwater)

0,327 mg/l (aqua, intermittent releases)

0,327 mg/l (aqua, marine water)

12,46 mg/kg (sediment marine water)

100-41-4 ethylbenzene

PNEC 9,6 mg/l (STP)

0,1 mg/l (aqua, freshwater)

0,1 mg/l (aqua, intermittent releases)

0,01 mg/l (aqua, marine water)

13,7 mg/kg (sediment freshwater)

2,68 mg/kg (soil)

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Thickness of the gloves ≥ 0.3 mm (butylacetate)Value for the permeation: Level ≥ 60 min (butylacetate)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:

Fluid

Colour:

White

· Odour:

Characteristic

· Odour threshold:

Not determined.

(Contd. on page 5)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.06.2015

Version number 5

Revision: 15.06.2015

Trade name: **KRISTAL UHS Surfacer 53 White**

(Contd. of page 4)

· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	124 °C
· Flash point:	25 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	370 °C
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1,2 Vol %
Upper:	7,5 Vol %
· Vapour pressure at 20 °C:	10,7 hPa
· Density at 20 °C:	1,57 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Slightly soluble.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic at 20 °C:	12 Poise
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	28,9 %
VOC (EC)	28,87 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Reacts with strong oxidizing agents.
- 10.4 Conditions to avoid High temperatures.
- 10.5 Incompatible materials:
 - Acids.
 - Alkaline products.
 - Oxidizing agents.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity
- LD/LC50 values relevant for classification:

123-86-4 n-butyl acetate

Oral	LD50	10760 mg/kg (rat) (OECD 423)
Dermal	LD50	>14112 mg/kg (rabbit) (OECD 402)

(Contd. on page 6)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.06.2015

Version number 5

Revision: 15.06.2015

Trade name: **KRISTAL UHS Surfacer 53 White**

(Contd. of page 5)

Inhalative LC50/4h 23,4 mg/l (rat) (OECD 403 in vivo, aerosol)

1330-20-7 xylene

Oral LD50 3523 mg/kg (rat)

Dermal LD50 12126 mg/kg bw (rabbit)

Inhalative LC50/4h 27124 mg/m³ (rat)**64742-95-6 Solvent naphtha (petroleum), light arom.**

Oral LD50 >6800 mg/kg (rat)

Dermal LD50 >3400 mg/kg (rab)

Inhalative LC50/4h >10,2 mg/l (rat)

100-41-4 ethylbenzene

Oral LD50 3500 mg/kg (rat)

Dermal LD50 17800 mg/kg (rabbit)

- Primary irritant effect:
- Skin corrosion/irritation No irritant effect.
- Serious eye damage/irritation No irritating effect.
- Respiratory or skin sensitisation No sensitising effects known.

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity:

123-86-4 n-butyl acetate

EC50/48h 44 mg/l (daphnia magna)

EC50/72h 647,7 mg/l (desmodesmus supspicatus)

IC50 356 mg/l (tetrahymena pyriformis) (40 h)

LC50/96h 18 mg/l (pimphales promelas) (OECD 203)

NOAEL/72h 200 mg/l (desmodesmus supspicatus)

1330-20-7 xylene

EC50/48h 7,4 mg/l (daphnia magna)

IC50 1-10 mg/l (TISBE Marine copepod)

1-10 mg/l (algae)

> 100 mg/l (bacteria)

1-10 mg/l (fish)

NOAEL 0,1-1 mg/l (TISBE Marine copepod)

1-10 mg/l (fish)

100-41-4 ethylbenzene

EC50/24h >100 mg/l (daphnia magna)

- 12.2 Persistence and degradability No further relevant information available.
- Degree of elimination:

123-86-4 n-butyl acetate

OECD 301D 83 % (l) (28 d)

- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Ecotoxicological effects:

- Remark: Harmful to fish
- Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.06.2015

Version number 5

Revision: 15.06.2015

Trade name: **KRISTAL UHS Surfacer 53 White**

(Contd. of page 6)

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
 - Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.
 - European waste catalogue
-
- 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances
- Uncleaned packaging:
 - Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- 14.1 UN-Number
- ADR,ADN, IMDG, IATA
- 14.2 UN proper shipping name
- ADR/ADN
- IMDG, IATA
- 14.3 Transport hazard class(es)
- ADR,ADN, IMDG, IATA

UN1263

1263 PAINT

PAINT



- Class
- Label
- 14.4 Packing group
- ADR,ADN, IMDG, IATA
- 14.5 Environmental hazards:
- Marine pollutant:
- 14.6 Special precautions for user
- Danger code (Kemler):
- EMS Number:
- 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
- Transport/Additional information:

3 Flammable liquids.

3

III

No

Warning: Flammable liquids.

30

F-E,S-E

Not applicable.

-
- ADR/ADN
 - Limited quantities (LQ)
 - Excepted quantities (EQ)
 - Transport category
 - Tunnel restriction code

5L

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

3

D/E

-
- IMDG
 - Limited quantities (LQ)
 - Excepted quantities (EQ)
 - UN "Model Regulation":

5L

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

UN1263, PAINT, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.

(Contd. on page 8)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.06.2015

Version number 5

Revision: 15.06.2015

Trade name: KRISTAL UHS Surfacer 53 White

(Contd. of page 7)

- National regulations:

- Other regulations, limitations and prohibitive regulations

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.

- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

- Contact: Dhr. B. Peters

- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

— EU —