



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 10.03.2015

Version number 5

Revision: 10.03.2015

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: **KRISTAL MS Clear Coat 91 2:1**
- Article number: 9110
- 1.2 Relevant identified uses of the substance or mixture and uses advised against  
No further relevant information available.
- Application of the substance / the mixture Lacquer
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:  
Kristal Coatings B.V.  
Platinawerf 22B  
6641 TL Beuningen - Holland  
Tel: 0031 24 67 526 36  
Fax: 0031 24 67 533 60
- Further information obtainable from: Product safety department: info@kristalcoatings.nl
- 1.4 Emergency telephone number:  
National Poisoning Information Centre - Bilthoven - The Netherlands  
T +31 (0)30 274 88 88  
Restricted to physicians for information on ingredients.

### SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3      H226 Flammable liquid and vapour.



GHS07

Eye Irrit. 2      H319 Causes serious eye irritation.  
Skin Sens. 1      H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xn; Harmful

R20:              Harmful by inhalation.



Xi; Irritant

R36/37:          Irritating to eyes and respiratory system.



Xi; Sensitising

R43:              May cause sensitisation by skin contact.

R10-52/53-66: Flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
Repeated exposure may cause skin dryness or cracking.

- Information concerning particular hazards for human and environment:  
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.  
At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
- Classification system:  
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008  
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)  
EU



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 10.03.2015

Version number 5

Revision: 10.03.2015

Trade name: **KRISTAL MS Clear Coat 91 2:1**

(Contd. of page 1)

## · Hazard pictograms



GHS02

GHS07

## · Signal word Warning

## · Hazard-determining components of labelling:

polyacrylate

Mix of: Reaction mass of Poly(oxy-1,2-ethanediyl),  
.alpha.-[3-[3-(2H-benzotriazol-2-yl)-5--(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy- and Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

## · Hazard statements

H226 Flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H412 Harmful to aquatic life with long lasting effects.

## · Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P260 Do not breathe mist/vapours/spray.  
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

## · Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.  
Restricted to professional users.

## · 2.3 Other hazards

## · Results of PBT and vPvB assessment

· PBT: Not applicable.  
· vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

## · 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

## · Dangerous components:

CAS: 37237-99-3	polyacrylate Xi R43 Skin Sens. 1, H317	25-50%
CAS: 108-10-1 EINECS: 203-550-1 Reg.nr.: 01-2119473980-30	4-methylpentan-2-one Xn R20;  Xi R36/37;  F R11 R66 Flam. Liq. 2, H225;  Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335	10-25%
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light aromatic Xn R65;  Xi R37;  N R51/53 R10-66-67 Flam. Liq. 3, H226;  Asp. Tox. 1, H304;  Aquatic Chronic 2, H411;  Acute Tox. 4, H332; STOT SE 3, H335-H336	10-25%

(Contd. on page 3)

EU



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 10.03.2015

Version number 5

Revision: 10.03.2015

Trade name: **KRISTAL MS Clear Coat 91 2:1**

(Contd. of page 2)

CAS: 1330-20-7	xylene	2,5-10%
EINECS: 215-535-7	☒ Xn R20/21-65; ☒ Xi R36/37/38	
Reg.nr.: 01-2119488216-32	R10	
01-2119486136-34	⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312;	
01-2119555267-33	Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	0,5-2,5%
EINECS: 265-199-0	☒ Xn R65; ☒ Xi R37; ☒ N R51/53	
Reg.nr.: 01-2119455851-35	R10-66-67	
	⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H332; STOT SE 3, H335-H336	
CAS: 100-41-4	ethylbenzene	0,5-2,5%
EINECS: 202-849-4	☒ Xn R20; ☒ F R11	
Reg.nr.: 01-2119489370-35	⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 4, H332	
CAS: 123-86-4	n-butyl acetate	0,5-2,5%
EINECS: 204-658-1	R10-66-67	
Reg.nr.: 01-2119485493-29	⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	
ELINCS: 400-830-7	Mix of: Reaction mass of Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- .omega.-hydroxy- and Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]- ☒ Xi R43; ☒ N R51/53 ⚠ Aquatic Chronic 2, H411; ⚠ Skin Sens. 1, H317	≤ 0,5%
CAS: 41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	≤ 0,5%
EINECS: 255-437-1	☒ Xi R43; ☒ N R50/53	
Reg.nr.: 01-2119491304-40	⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Sens. 1, H317	
· Additional information: For the wording of the listed risk phrases refer to section 16.		

## SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information:
  - Immediately remove any clothing soiled by the product.
  - Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation:
  - Supply fresh air and to be sure call for a doctor.
  - In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
  - Remove contactlenses.
  - Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing:
  - Rinse mouth.
  - Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
  - No further relevant information available.

## SECTION 5: Firefighting measures

- 5.1 Extinguishing media
  - Suitable extinguishing agents: CO<sub>2</sub> or powder. Fight larger fights with alcohol resistant foam.
  - For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Carbon monoxide (CO)
- 5.3 Advice for firefighters
  - Protective equipment: Wear self-contained respiratory protective device.



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 10.03.2015

Version number 5

Revision: 10.03.2015

Trade name: **KRISTAL MS Clear Coat 91 2:1**

(Contd. of page 3)

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Inform respective authorities in case of seepage into water course or sewage system.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.
- **Information about storage in one common storage facility:**  
Do not store together with alkalis (caustic solutions).  
Do not store together with oxidising and acidic materials.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

#### 8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

##### **108-10-1 4-methylpentan-2-one**

IOELV Short-term value: 208 mg/m<sup>3</sup>, 50 ppm  
Long-term value: 83 mg/m<sup>3</sup>, 20 ppm

##### **1330-20-7 xylene**

IOELV Short-term value: 442 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 221 mg/m<sup>3</sup>, 50 ppm  
Skin

##### **100-41-4 ethylbenzene**

IOELV Short-term value: 884 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 442 mg/m<sup>3</sup>, 100 ppm  
Skin

- **DNELs**

##### **108-10-1 4-methylpentan-2-one**

Dermal	Long-term exposure - systemic effects	11,8 mg/kg bw/day (worker)
Inhalative	Acute - short-term exposure - local effects	208 mg/m <sup>3</sup> (worker)
	Acute - short-term exposure - systemic effects	208 mg/m <sup>3</sup> (worker)
	Long-term exposure - local effects	83 mg/m <sup>3</sup> (worker)
	Long-term exposure - systemic effects	83 mg/m <sup>3</sup> (worker)

##### **1330-20-7 xylene**

Dermal	Long-term exposure - systemic effects	180 mg/kg bw/day (worker)
Inhalative	Acute - short-term exposure - local effects	289 mg/m <sup>3</sup> (worker)
	Acute - short-term exposure - systemic effects	289 mg/m <sup>3</sup> (worker)

(Contd. on page 5)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 10.03.2015

Version number 5

Revision: 10.03.2015

Trade name: **KRISTAL MS Clear Coat 91 2:1**

(Contd. of page 4)

Long-term exposure - systemic effects 77 mg/m3 (worker)

**100-41-4 ethylbenzene**

Dermal Acute - short-term exposure - local effects 293 mg/kg bw/day (worker)

Long-term exposure - systemic effects 180 mg/kg bw/day (worker)

Inhalative Long-term exposure - systemic effects 77 mg/m3 (worker)

**123-86-4 n-butyl acetate**

Inhalative Acute - short-term exposure - local effects 960 mg/m3 (worker)

Acute - short-term exposure - systemic effects 960 mg/m3 (worker)

Long-term exposure - local effects 480 mg/m3 (worker)

Long-term exposure - systemic effects 480 mg/m3 (worker)

· **PNECs****108-10-1 4-methylpentan-2-one**

PNEC 27,5 mg/l (STP)

0,6 mg/l (aqua, freshwater)

1,5 mg/l (aqua, intermittent releases)

0,06 mg/l (aqua, marine water)

0,83 mg/kg (sediment marine water)

8,27 mg/kg (sediment freshwater)

**1330-20-7 xylene**

PNEC 6,58 mg/l (STP)

0,237 mg/l (aqua, freshwater)

0,327 mg/l (aqua, intermittent releases)

0,327 mg/l (aqua, marine water)

12,46 mg/kg (sediment marine water)

**100-41-4 ethylbenzene**

PNEC 9,6 mg/l (STP)

0,1 mg/l (aqua, freshwater)

0,1 mg/l (aqua, intermittent releases)

0,01 mg/l (aqua, marine water)

13,7 mg/kg (sediment freshwater)

2,68 mg/kg (soil)

**123-86-4 n-butyl acetate**

PNEC 35,6 mg/l (STP)

0,18 mg/l (aqua, freshwater)

0,36 mg/l (aqua, intermittent releases)

0,018 mg/l (aqua, marine water)

0,0981 mg/l (sediment marine water)

0,981 mg/kg (sediment freshwater)

· **Additional information:** The lists valid during the making were used as basis.· **8.2 Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A.

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product.

(Contd. on page 6)



Printing date 10.03.2015

## Safety data sheet according to 1907/2006/EC, Article 31

Version number 5

Revision: 10.03.2015

Trade name: **KRISTAL MS Clear Coat 91 2:1**

(Contd. of page 5)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Polyethylene gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**Thickness of the gloves  $\geq 0.06$  mm (methyl isobutyl ketone)Value for the permeation: Level  $\geq 480$  min (methyl isobutyl ketone)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Tightly sealed goggles

· **Body protection:** Solvent resistant protective clothing

### SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**· **General Information**· **Appearance:**

Form: Fluid

Colour: Clear

· **Odour:** Characteristic· **Change in condition**

Boiling point/Boiling range: 116 °C

· **Flash point:** 25 °C· **Ignition temperature:** 450 °C· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.· **Explosion limits:**

Lower: 0,7 Vol %

Upper: 9,0 Vol %

· **Vapour pressure at 20 °C:** 8 hPa· **Density at 20 °C:** 0,98 g/cm<sup>3</sup>· **Solubility in / Miscibility with water:** Insoluble.· **Viscosity:**

Dynamic: Not determined.

Kinematic at 20 °C:  $\pm 44$  s (DIN 53211/4)· **Solvent content:**

Organic solvents: 42,3 %

VOC (EC) 44,51 %

Solids content: 56,9 %

· **9.2 Other information** No further relevant information available.

### SECTION 10: Stability and reactivity

· **10.1 Reactivity**· **10.2 Chemical stability**· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.· **10.3 Possibility of hazardous reactions** No dangerous reactions known.· **10.4 Conditions to avoid** No further relevant information available.

(Contd. on page 7)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 10.03.2015

Version number 5

Revision: 10.03.2015

Trade name: **KRISTAL MS Clear Coat 91 2:1**

(Contd. of page 6)

- 10.5 Incompatible materials:
  - Oxidizing agents.
  - Alkaline products.
  - Acids.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity:
- LD/LC50 values relevant for classification:

### 108-10-1 4-methylpentan-2-one

Oral LD50 2080 mg/kg (rat)  
 Dermal LD50 >2000 mg/kg (rabbit)  
 Inhalative LC50/4h 8,2-16,4 mg/l (rat)

### 64742-95-6 Solvent naphtha (petroleum), light aromatic

Oral LD50 >6800 mg/kg (rat)  
 Dermal LD50 >3400 mg/kg (rab)  
 Inhalative LC50/4h >10,2 mg/l (rat)

### 1330-20-7 xylene

Oral LD50 3523 mg/kg (rat)  
 Dermal LD50 12126 mg/kg bw (rabbit)  
 Inhalative LC50/4h 27124 mg/m3 (rat)

### 64742-95-6 Solvent naphtha (petroleum), light arom.

Oral LD50 >6800 mg/kg (rat)  
 Dermal LD50 >3400 mg/kg (rab)  
 Inhalative LC50/4h >10,2 mg/l (rat)

### 100-41-4 ethylbenzene

Oral LD50 3500 mg/kg (rat)  
 Dermal LD50 17800 mg/kg (rabbit)

### 123-86-4 n-butyl acetate

Oral LD50 10760 mg/kg (rat) (OECD 423)  
 Dermal LD50 >14112 mg/kg (rabbit) (OECD 402)  
 Inhalative LC50/4h 23,4 mg/l (rat) (OECD 403 in vivo, aerosol)

### Mix of: Reaction mass of Poly(oxy-1,2-ethanediyl),

.alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy- and Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-

Oral LD50 >5000 mg/kg (rat) (OESO 401)  
 Dermal LD50 >2000 ml/kg (rat) (OESO 402)

- Primary irritant effect:
  - on the skin: No irritant effect.
  - on the eye: No irritating effect.
- Sensitisation: Sensitisation possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful  
 Irritant

## SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity:

### 108-10-1 4-methylpentan-2-one

EC50/48h >200 mg/l (daphnia magna)  
 EC50/96h 400 mg/l (algae)

(Contd. on page 8)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 10.03.2015

Version number 5

Revision: 10.03.2015

Trade name: **KRISTAL MS Clear Coat 91 2:1**

(Contd. of page 7)

LC50/96h &gt;179 mg/l (fish)

**1330-20-7 xylene**

EC50/48h 7,4 mg/l (daphnia magna)

IC50 1-10 mg/l (TISBE Marine copepod)

1-10 mg/l (algae)

&gt; 100 mg/l (bacteria)

1-10 mg/l (fish)

NOAEL 0,1-1 mg/l (TISBE Marine copepod)

1-10 mg/l (fish)

**100-41-4 ethylbenzene**

EC50/24h &gt;100 mg/l (daphnia magna)

**123-86-4 n-butyl acetate**

EC50/48h 44 mg/l (daphnia magna)

EC50/72h 647,7 mg/l (desmodesmus supspicatus)

IC50 356 mg/l (tetrahymena pyriformis) (40 h)

LC50/96h 18 mg/l (pimphales promelas) (OECD 203)

NOAEL/72h 200 mg/l (desmodesmus supspicatus)

**Mix of: Reaction mass of Poly(oxy-1,2-ethanediyl),**

**.alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy- and Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-**

EC50/48h 4,0 mg/l (daphnia magna) (OESO 202)

EC50/72h &gt;9 mg/l (algae)

LC50/14d &gt;5800 mg/kg (rat) (OESO 403)

LC50/96h 2,8 mg/l (oncorhynchus mykiss) (OESO 203)

· 12.2 Persistence and degradability No further relevant information available.

· Degree of elimination:

**123-86-4 n-butyl acetate**

OECD 301D 83 % (/) (28 d)

· 12.3 Bioaccumulative potential No further relevant information available.

· 12.4 Mobility in soil No further relevant information available.

· Ecotoxicological effects:

· Remark: Harmful to fish

· Additional ecological information:

· General notes: Harmful to aquatic organisms

· 12.5 Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

· 12.6 Other adverse effects No further relevant information available.

---

## SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

---

## SECTION 14: Transport information

· 14.1 UN-Number

· ADR,ADN, IMDG, IATA

UN1263

· 14.2 UN proper shipping name

· ADR/ADN

1263 PAINT

· IMDG, IATA

PAINT

(Contd. on page 9)





Printing date 10.03.2015

## Safety data sheet

### according to 1907/2006/EC, Article 31

Version number 5

Revision: 10.03.2015

Trade name: **KRISTAL MS Clear Coat 91 2:1**

(Contd. of page 8)

- 14.3 Transport hazard class(es)
- ADR,ADN, IMDG, IATA



- Class 3 Flammable liquids.
- Label 3
- 14.4 Packing group
- ADR,ADN, IMDG, IATA III
- 14.5 Environmental hazards:
- Marine pollutant: No
- 14.6 Special precautions for user Warning: Flammable liquids.
- Danger code (Kemler): 30
- EMS Number: F-E,S-E
- 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

- Transport/Additional information:

- ADR/ADN
- Limited quantities (LQ) 5L
- Excepted quantities (EQ) Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml
- Transport category 3
- Tunnel restriction code D/E

- IMDG
- Limited quantities (LQ) 5L
- Excepted quantities (EQ) Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml
- UN "Model Regulation": UN1263, PAINT, 3, III

## SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- National regulations:
- Other regulations, limitations and prohibitive regulations  
The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

(Contd. on page 10)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 10.03.2015

Version number 5

Revision: 10.03.2015

Trade name: **KRISTAL MS Clear Coat 91 2:1**

(Contd. of page 9)

H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
R10	Flammable.
R11	Highly flammable.
R20	Harmful by inhalation.
R20/21	Harmful by inhalation and in contact with skin.
R36/37	Irritating to eyes and respiratory system.
R36/37/38	Irritating to eyes, respiratory system and skin.
R37	Irritating to respiratory system.
R43	May cause sensitisation by skin contact.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

· Department issuing MSDS: Product safety department.

· Contact: Dhr. B. Peters

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 ICAO: International Civil Aviation Organisation  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 VOC: Volatile Organic Compounds (USA, EU)  
 DNEL: Derived No-Effect Level (REACH)  
 PNEC: Predicted No-Effect Concentration (REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 Flam. Liq. 2: Flammable liquids, Hazard Category 2  
 Flam. Liq. 3: Flammable liquids, Hazard Category 3  
 Acute Tox. 4: Acute toxicity, Hazard Category 4  
 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2  
 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2  
 Skin Sens. 1: Sensitisation - Skin, Hazard Category 1  
 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3  
 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2  
 Asp. Tox. 1: Aspiration hazard, Hazard Category 1  
 Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1  
 Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1  
 Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2  
 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

EU