



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.04.2021

Version number 1

Revision: 08.04.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: **ZENITH HS420 Hardener Air-Dry**
- Article number: Z8203
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use
 - SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- Application of the substance / the mixture Hardening agent/ Curing agent
- Uses advised against SU21 Consumer uses: Private households / general public / consumers
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
 - Kristal Coatings B.V.
 - Platinawerf 22B
 - 6641 TL Beuningen - Holland
 - Tel: 0031 24 67 526 36
 - Fax: 0031 24 67 533 60
- Further information obtainable from: Product safety department: info@kristalcoatings.nl
- 1.4 Emergency telephone number:
 - National Poisoning Information Centre - Bilthoven - The Netherlands
 - T +31 (0)30 274 88 88
 - Restricted to physicians for information on ingredients.

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

STOT RE 2 H373 May cause damage to the central nervous system, the kidneys and the liver through prolonged or repeated exposure. Route of exposure: Inhalation.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
 - The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



GHS02



GHS07



GHS08

- Signal word Danger
- Hazard-determining components of labelling:
 - Reaction mass of ethylbenzene and xylene

(Contd. on page 2)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.04.2021

Version number 1

Revision: 08.04.2021

Trade name: **ZENITH HS420 Hardener Air-Dry**

(Contd. of page 1)

Hexamethylene diisocyanate, oligomers

Hydrocarbons, C9, aromatics

4-methylpentan-2-one

hexamethylene-di-isocyanate

Hazard statements

H225 Highly flammable liquid and vapour.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H373 May cause damage to the central nervous system, the kidneys and the liver through prolonged or repeated exposure. Route of exposure: Inhalation.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Additional information:

EUH204 Contains isocyanates. May produce an allergic reaction.

Restricted to professional users.

2.3 Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures**

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components %(m/m):

EC number: 905-588-0	Reaction mass of ethylbenzene and xylene	25-50%
Reg.nr.: 01-2119488216-32	⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 28182-81-2	Hexamethylene diisocyanate, oligomers	25-50%
NLP: 500-060-2	⚠ Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	
Reg.nr.: 01-2119485796-17		
CAS: 141-78-6	ethyl acetate	2.5-10%
EINECS: 205-500-4	⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	
Reg.nr.: 01-2119475103-46		
CAS: 108-10-1	4-methylpentan-2-one	2.5-10%
EINECS: 203-550-1	⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335	
Reg.nr.: 01-2119473980-30		
CAS: 123-86-4	n-butyl acetate	0.5-2.5%
EINECS: 204-658-1	⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	
Reg.nr.: 01-2119485493-29		
Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics	0.5-2.5%
	⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336	
CAS: 108-88-3	toluene	≤0.5%
EINECS: 203-625-9	⚠ Flam. Liq. 2, H225; ⚠ Repr. 1B, H360; Asp. Tox. 1, H304; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336; Aquatic Chronic 3, H412	
Reg.nr.: 01-2119471310-51		
CAS: 77-58-7	dibutyltin dilaurate	≤0.5%
EINECS: 201-039-8	⚠ Muta. 2, H341; Repr. 1B, H360FD; STOT RE 1, H372	
Reg.nr.: 01-2119496068-27		

Additional information: For the wording of the listed hazard phrases refer to section 16.



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.04.2021

Version number 1

Revision: 08.04.2021

Trade name: **ZENITH HS420 Hardener Air-Dry**

(Contd. of page 2)

SECTION 4: First aid measures

- 4.1 Description of first aid measures
 - General information:
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
 - After inhalation:
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
 - After skin contact:
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
 - After eye contact:
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
Remove contactlenses.
 - After swallowing:
Do not induce vomiting; call for medical help immediately.
Rinse out mouth and then drink plenty of water.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
 - Suitable extinguishing agents: CO₂ or powder. Fight larger fights with alcohol resistant foam.
 - For safety reasons unsuitable extinguishing agents:
Water with full jet
Water spray
- 5.2 Special hazards arising from the substance or mixture
During heating or in case of fire poisonous gases are produced.
Carbon monoxide (CO)
- 5.3 Advice for firefighters
- Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Collect leaking fluid in lockable waste containers.
- 6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
Persons with a history of asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is used.
Examination of lung function should be carried out on a regular basis on persons spraying this preparation.
- Information about fire - and explosion protection:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.

(Contd. on page 4)

— EU —



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.04.2021

Version number 1

Revision: 08.04.2021

Trade name: **ZENITH HS420 Hardener Air-Dry**

(Contd. of page 3)

- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
 - Requirements to be met by storerooms and receptacles:
 - Store in a cool location.
 - Store only in the original receptacle.
 - Information about storage in one common storage facility: Store away from oxidising agents.
 - Further information about storage conditions: Keep container tightly sealed.
- Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters
- Additional information about design of technical facilities: No further data; see item 7.
- Ingredients with limit values that require monitoring at the workplace:

141-78-6 ethyl acetate

IOELV Short-term value: 1468 mg/m³, 400 ppm
 Long-term value: 734 mg/m³, 200 ppm

108-10-1 4-methylpentan-2-one

IOELV Short-term value: 208 mg/m³, 50 ppm
 Long-term value: 83 mg/m³, 20 ppm

123-86-4 n-butyl acetate

IOELV Short-term value: 723 mg/m³, 150 ppm
 Long-term value: 241 mg/m³, 50 ppm

108-88-3 toluene

IOELV Short-term value: 384 mg/m³, 100 ppm
 Long-term value: 192 mg/m³, 50 ppm
 Skin

- DNELs

Reaction mass of ethylbenzene and xylene

Dermal	Long-term exposure - systemic effects	212 mg/kg bw/day (worker)
Inhalative	Acute - short-term exposure - systemic effects	442 mg/m ³ (worker)
	Acute - short-term exposure - local effects	442 mg/m ³ (worker)
	Long-term exposure - systemic effects	221 mg/m ³ (worker)
	Long-term exposure - local effects	221 mg/m ³ (worker)

28182-81-2 Hexamethylene diisocyanate, oligomers

Dermal	Acute - short-term exposure - local effects	1 mg/cm ² (worker)
Inhalative	Long-term exposure - local effects	0.5 mg/m ³ (worker)

141-78-6 ethyl acetate

Dermal	Long-term exposure - systemic effects	63 mg/kg bw/day (worker)
Inhalative	Acute - short-term exposure - systemic effects	1,468 mg/m ³ (worker)
	Acute - short-term exposure - local effects	1,468 mg/m ³ (worker)
	Long-term exposure - systemic effects	734 mg/m ³ (worker)
	Long-term exposure - local effects	734 mg/m ³ (worker)

108-10-1 4-methylpentan-2-one

Dermal	Long-term exposure - systemic effects	11.8 mg/kg bw/day (worker)
Inhalative	Acute - short-term exposure - systemic effects	208 mg/m ³ (worker)
	Acute - short-term exposure - local effects	208 mg/m ³ (worker)
	Long-term exposure - systemic effects	83 mg/m ³ (worker)
	Long-term exposure - local effects	83 mg/m ³ (worker)

123-86-4 n-butyl acetate

Inhalative	Acute - short-term exposure - systemic effects	600 mg/m ³ (worker)
	Acute - short-term exposure - local effects	600 mg/m ³ (worker)
	Long-term exposure - systemic effects	300 mg/m ³ (worker)
	Long-term exposure - local effects	300 mg/m ³ (worker)

(Contd. on page 5)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.04.2021

Version number 1

Revision: 08.04.2021

Trade name: **ZENITH HS420 Hardener Air-Dry**

(Contd. of page 4)

Hydrocarbons, C9, aromaticsInhalative Long-term exposure - systemic effects 261.88 mg/m³ (worker)**108-88-3 toluene**

Dermal Long-term exposure - systemic effects 384 mg/kg bw/day (worker)

Inhalative Acute - short-term exposure - systemic effects 384 mg/m³ (worker)Acute - short-term exposure - local effects 384 mg/m³ (worker)Long-term exposure - systemic effects 192 mg/m³ (worker)Long-term exposure - local effects 192 mg/m³ (worker)**77-58-7 dibutyltin dilaurate**

Dermal Long-term exposure - systemic effects 0.43 mg/kg bw/day (worker)

Inhalative Long-term exposure - systemic effects 0.02 mg/m³ (worker)**PNECs****Reaction mass of ethylbenzene and xylene**

PNEC 12.46 mg/kg (sediment marine water)

12.46 mg/kg (sediment freshwater)

2.31 mg/kg (soil)

PNEC 6.58 mg/l (STP)

0.327 mg/l (aqua, freshwater)

0.327 mg/l (aqua, marine water)

28182-81-2 Hexamethylene diisocyanate, oligomers

PNEC 26,670 mg/kg (aqua, marine water)

53,182 mg/kg (bd)

266,700 mg/kg (sediment freshwater)

PNEC 38.28 mg/l (STP)

0.127 mg/l (aqua, freshwater)

1.27 mg/l (aqua, intermittent releases)

0.0127 mg/l (aqua, marine water)

141-78-6 ethyl acetate

PNEC 0.115 mg/kg (sediment marine water)

1.15 mg/kg (sediment freshwater)

0.148 mg/kg (soil)

PNEC 650 mg/l (STP)

0.24 mg/l (aqua, freshwater)

1.65 mg/l (aqua, intermittent releases)

0.024 mg/l (aqua, marine water)

108-10-1 4-methylpentan-2-one

PNEC 0.83 mg/kg (sediment marine water)

8.27 mg/kg (sediment freshwater)

1.3 mg/kg (soil)

PNEC 27.5 mg/l (STP)

0.6 mg/l (aqua, freshwater)

1.5 mg/l (aqua, intermittent releases)

0.06 mg/l (aqua, marine water)

123-86-4 n-butyl acetate

PNEC mg/kg (rat)

0.981 mg/kg (sediment freshwater)

PNEC 35.6 mg/l (STP)

0.18 mg/l (aqua, freshwater)

0.36 mg/l (aqua, intermittent releases)

0.018 mg/l (aqua, marine water)

0.0981 mg/l (sediment marine water)

108-88-3 toluene

PNEC 16.39 mg/kg (sediment marine water)

(Contd. on page 6)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.04.2021

Version number 1

Revision: 08.04.2021

Trade name: **ZENITH HS420 Hardener Air-Dry**

(Contd. of page 5)

16.39 mg/kg (sediment freshwater)

2.89 mg/kg (soil)

PNEC 13.61 mg/l (STP)

0.68 mg/l (aqua, freshwater)

0.68 mg/l (aqua, intermittent releases)

0.68 mg/l (aqua, marine water)

77-58-7 dibutyltin dilaurate

PNEC 0.2 mg/kg (food)

0.005 mg/kg (sediment marine water)

0.041 mg/kg (soil)

PNEC 100 mg/l (STP)

0 mg/l (aqua, freshwater)

0 mg/l (aqua, marine water)

Additional Occupational Exposure Limit Values for possible hazards during processing:**1330-20-7 xylene**IOELV Short-term value: 442 mg/m³, 100 ppmLong-term value: 221 mg/m³, 50 ppm

Skin

100-41-4 ethylbenzeneIOELV Short-term value: 884 mg/m³, 200 ppmLong-term value: 442 mg/m³, 100 ppm

Skin

Additional information:

The lists valid during the making were used as basis.

Persons with a history of asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is used.

Examination of lung function should be carried out on a regular basis on persons spraying this preparation.

8.2 Exposure controls**Personal protective equipment:****General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter A.

Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Suitable materials for safety gloves (EN 374):

Fluorocarbon rubber gloves (Viton)

Penetration time of glove materialThickness of the gloves \geq 0.7 mm (xylenes)Value for the permeation \geq 480 min (xylenes)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Tightly sealed goggles

(Contd. on page 7)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.04.2021

Version number 1

Revision: 08.04.2021

Trade name: **ZENITH HS420 Hardener Air-Dry**

(Contd. of page 6)

· Body protection: Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid

Colour: Clear

· Odour: Characteristic

· Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: ≥ 77 - ≤ 78 °C (141-78-6 ethyl acetate)

· Flash point: 7-10 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: ≥ 460 °C (141-78-6 ethyl acetate)

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower: ≥ 1.1 Vol % (Reaction mass of ethylbenzene and xylene)Upper: ≤ 7 Vol % (Reaction mass of ethylbenzene and xylene)· Vapour pressure at 20 °C: ≥ 6.7 - ≤ 8.2 hPa (Reaction mass of ethylbenzene and xylene)· Density at 20 °C: 0.96 g/cm³

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with water:

Slightly soluble.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined.

Kinematic at 20 °C: 10 s (DIN 53211/4)

· Solvent content:

Organic solvents: 61.6 %

VOC (EC) 61.56 %

· 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions

Reacts with alcohols.

Reacts with amines.

Reacts with water.

Reacts with strong oxidizing agents.

(Contd. on page 8)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.04.2021

Version number 1

Revision: 08.04.2021

Trade name: **ZENITH HS420 Hardener Air-Dry**

(Contd. of page 7)

- 10.4 Conditions to avoid High temperatures.
- 10.5 Incompatible materials: Oxidizing agents
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects

Acute toxicity

Harmful if inhaled.

- LD/LC50 values relevant for classification:

Reaction mass of ethylbenzene and xylene

Oral LD50 3,523 mg/kg (rat)

Dermal LD50 12,126 mg/kg bw (rabbit)

Inhalative LC50/4h 27,124 mg/m³ (rat)

141-78-6 ethyl acetate

Oral LD50 4,100 mg/kg (mouse)

Dermal LD50 5,620 mg/kg (rat)

>20,000 mg/kg (rabbit)

Inhalative LC50/4h 30 mg/l (rat)

108-10-1 4-methylpentan-2-one

Oral LD50 2,080 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rabbit)

Inhalative LC50/4h 8.2-16.4 mg/l (rat)

123-86-4 n-butyl acetate

Oral LD50 10,760 mg/kg (rat) (OECD 423)

Dermal LD50 >14,112 mg/kg (rabbit) (OECD 402)

Inhalative LC50/4h 23.4 mg/l (rat) (OECD 403 in vivo, aerosol)

108-88-3 toluene

Oral LD50 5,580 mg/kg (rat)

Dermal LD50 >5,000 mg/kg (rabbit)

Inhalative LC50/4h 28.1 mg/l (rat)

77-58-7 dibutyltin dilaurate

Oral LD50 2,071 mg/kg (rat) (OECD 401)

Dermal LD50 >2,000 mg/kg (rabbit) (OECD 402)

- Primary irritant effect:

- Skin corrosion/irritation

May cause an allergic skin reaction.

Causes skin irritation.

- Serious eye damage/irritation

Causes serious eye irritation.

- Respiratory or skin sensitisation

May cause an allergic skin reaction.

- Additional toxicological information:

- Sensitisation May cause sensitisation by skin contact.

- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

- Germ cell mutagenicity Based on available data, the classification criteria are not met.

- Carcinogenicity Based on available data, the classification criteria are not met.

- Reproductive toxicity Based on available data, the classification criteria are not met.

- STOT-single exposure

May cause respiratory irritation.

- STOT-repeated exposure

May cause damage to the central nervous system, the kidneys and the liver through prolonged or repeated exposure. Route of exposure: Inhalation.

- Aspiration hazard

May be fatal if swallowed and enters airways.



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.04.2021

Version number 1

Revision: 08.04.2021

Trade name: **ZENITH HS420 Hardener Air-Dry**

(Contd. of page 8)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

Reaction mass of ethylbenzene and xylene

Oral EC50/73h 2.2 mg/l (rat)
 EC50/48h 1 mg/l (daphnia magna)
 LC50/96h 2.6 mg/l (oncorhynchus mykiss)

141-78-6 ethyl acetate

NOEC/32d >9.65 mg/l (fish)
 NOEC/21d 2.4 mg/l (daphnia magna)
 EC50/48h 5,600 mg/l (algae)
 610 mg/l (daphnia magna)
 LC50/96h 230 mg/l (fish)

108-10-1 4-methylpentan-2-one

EC50/96h 400 mg/l (algae)
 EC50/48h >200 mg/l (daphnia magna)
 LC50/96h >179 mg/l (fish)

123-86-4 n-butyl acetate

EC50/48h 44 mg/l (daphnia magna)
 EC50/72h 647.7 mg/l (desmodesmus supspicatus)
 IC50 356 mg/l (tetrahymena pyriformis) (40 h)
 NOAEL/72h 200 mg/l (desmodesmus supspicatus)
 LC50/96h 18 mg/l (pimphales promelas) (OECD 203)

108-88-3 toluene

NOEC/72h 10 mg/l (Skeletonema costatum)
 EC50/3h 134 mg/l (Chlorella vulgaris)
 NOEC/7d 0.74 mg/l (Ceriodaphnia dubia)
 LOEC/7d 2.76 mg/l (Ceriodaphnia dubia)
 NOEC/40d 1.39 mg/l (Oncorhynchus kisutch)
 LOEC/40d 2.77 mg/l (Oncorhynchus kisutch)
 EC50/48h 3.78 mg/l (daphnia magna)
 EC50/7d 3.23 mg/l (Ceriodaphnia dubia)
 LC50/96h 5.5 mg/l (Oncorhynchus kisutch)

77-58-7 dibutyltin dilaurate

EC50/3h 1,000 mg/l (bacteria) (OECD 209)
 EC50/48h <1 mg/l (daphnia) (OECD 202)
 EC50/72h >1 mg/l (algae) (OECD 201)
 LC50/96h >3.1 mg/l (fish) (OECD 203)

12.2 Persistence and degradability No further relevant information available.

Degree of elimination:

141-78-6 ethyl acetate

OESO 303A >99.9 % (l) (OESO 303A)
 (readily biodegradable)

123-86-4 n-butyl acetate

OECD 301D 83 % (l) (28 d)

12.3 Bioaccumulative potential

Reaction mass of ethylbenzene and xylene

BCF 25.9 (l)
 LogPow <3.2 (l)

141-78-6 ethyl acetate

BCF 30 (leuciscus idus)

108-88-3 toluene

BCF 90 (l)

(Contd. on page 10)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.04.2021

Version number 1

Revision: 08.04.2021

Trade name: **ZENITH HS420 Hardener Air-Dry**

(Contd. of page 9)

LogPow 2.7 (/)

77-58-7 dibutyltin dilaurate

BCF 1.49-3.7 (/) (OECD 305)

LogPow 4.44 (/) (OECD 107)

· 12.4 Mobility in soil

141-78-6 ethyl acetate

Koc 1.43 (/)

· Other information:

141-78-6 ethyl acetate

BOD5/20d 79 (/)

· Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· 12.5 Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 05 01* waste isocyanates

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number

· ADR/ADN, IMDG, IATA

UN1263

· 14.2 UN proper shipping name

· ADR/ADN

1263 PAINT RELATED MATERIAL

· IMDG, IATA

PAINT RELATED MATERIAL

· 14.3 Transport hazard class(es)

· ADR/ADN, IMDG, IATA



· Class

3 Flammable liquids.

· Label

3

· 14.4 Packing group

· ADR/ADN, IMDG, IATA

II

· 14.5 Environmental hazards:

Not applicable.

· 14.6 Special precautions for user

Warning: Flammable liquids.

· Hazard identification number (Kemler code):

33

· EMS Number:

F-E,S-E

· Stowage Category

B

· 14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code

Not applicable.

(Contd. on page 11)

— EU —



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.04.2021

Version number 1

Revision: 08.04.2021

Trade name: **ZENITH HS420 Hardener Air-Dry**

(Contd. of page 10)

· Transport/Additional information:

· ADR/ADN

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· Transport category

2

· Tunnel restriction code

D/E

· IMDG

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation":

UN 1263 PAINT RELATED MATERIAL, 3, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 20, 48

· Regulation (EU) No 649/2012

77-58-7 dibutyltin dilaurate: Annex I Part 1

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· National regulations:

· Other regulations, limitations and prohibitive regulations

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H341 Suspected of causing genetic defects.

H360 May damage fertility or the unborn child.

H360FD May damage fertility. May damage the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

(Contd. on page 12)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.04.2021

Version number 1

Revision: 08.04.2021

Trade name: ZENITH HS420 Hardener Air-Dry

(Contd. of page 11)

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· **Contact:** Dhr. B. Peters· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Muta. 2: Germ cell mutagenicity – Category 2

Repr. 1B: Reproductive toxicity – Category 1B

Repr. 1B: Reproductive toxicity – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

— EU —