

Technical Data Sheet

2K Drying Booster
Art.nbr.: 3121

Special Products
Version: **EN-TDS-3121-4**
Revision: April 2015
Page: 1 of 3

FOR PROFESSIONAL USE ONLY

FULL TECHNICAL INFORMATION



- Drying accelerator for KRISTAL Clear Coats and Surfacer
- Can be also be used as universal drying accelerator in other 2K Clear Coats and Surfacer

FIELD OF APPLICATION

Improves surface drying and curing performance as well as tape resistance.

KRISTAL 2K Drying Booster is a drying accelerator for KRISTAL Clear Coats and Surfacer.

Technical Data Sheet

2K Drying Booster
Art.nbr.: 3121

Special Products
Version: **EN-TDS-3121-4**
Revision: April 2015
Page: 2 of 3

FOR PROFESSIONAL USE ONLY


PRODUCT AND AUXILIARY PRODUCTS

	2K Drying Booster	
Auxiliary products	2K PU Clear Coats 2K Surfacer	
Article numbers	2K Drying Booster	3121
	UHS Clear Coat 93 2:1	9310
	UHS Surfacer 53 5:1	
	Black	5325
	Dark Grey	5326
	Grey	5327
	White	5329
	HS Clear Coat 92 2:1 PLUS	9210+
	HS Surfacer 52 4:1 PLUS	
	Black	5225+
	Dark Grey	5226+
	Grey	5227+
	White	5229+
	ZENITH HS420 Clear Coat 2:1	Z9209
	ZENITH HS520 Surfacer 5:1	Z5200
	ZENITH HS Clear Coat Scratch-Resistant Z39 2:1	Z9039

CHEMICAL BASIS

KRISTAL 2K Drying Booster Mixture of aromates and acetates

MIXING



Add up to 10% 2K Drying Booster to the mix, instead of advised Thinner

PHYSICAL PROPERTIES

Density : 0,88/l
Flashpoint : 24 °C

VOLATILE ORGANIC COMPOUND

This product contains a maximum of 870 g/l. VOC

Technical Data Sheet

2K Drying Booster
Art.nbr.: 3121

Special Products
Version: **EN-TDS-3121-4**
Revision: April 2015
Page: 3 of 3

FOR PROFESSIONAL USE ONLY

STORAGE LIFE

Under normal storage conditions for up to two years in unopened tins.

TRANSPORT- AND STORAGE CONDITIONS

Do not store or transport this product at a temperature lower than 8°C or higher than 30°C.

KRISTAL COATINGS B.V.

P.O. Box 72
6640 AB BEUNINGEN GLD.
The NETHERLANDS

Tel.: +31 24 675 2636
Fax: +31 24 675 3360

E-mail: info@kristalcoatings.nl
Internet: www.kristalcoatings.com

Important notice

Our products are suitable for professional use only. Registered processing times are valid under conditioned application circumstances only. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, not the suitability of the products for a specific purpose. Any date, weight, proportions, etc. given herein are for general information purpose only; they may change without prior information and do not constitute the quality of the products (product specification).

For technical support and advice with concern to choices of coatings systems and methods of application, our technical staff will be at your service at all times.